



Differential pressure switch DS 01



Benefits

- Robust diaphragm type movement
- Suitable for overpressure, vacuum and differential pressure measurements

Application

Suitable for all practically neutral media such as process water, heating water, neutral gases, oils. Suitable for two-point control by means of a continuously adjustable switching point (between 10 and 100% of pressure range).

Description

A robust diaphragm type movement serves as the basis for this unit. It is suitable for overpressure, vacuum and differential pressure measurements. The unit uses the same principle of operation for all three measuring applications. The pressure or the differential pressure applies a force to one side of the diaphragm. This force displaces the diaphragm system and moves the measurement range spring. A switching pin mounted to the diaphragm actuates an electrical switching element. The switching point is set by means of a wheel with a scale.

Technical specifications

Pressure range

0/0.6 bar

0/1 bar

0/1.6 bar

0/2.5 bar

0/4 bar

Operating temperature range

Medium: Max. 80 °C

Ambient: Max. 80 °C

Brass

Diaphragm

NBR (Perbunan)

Electrical connection

Cable gland M12 x 1.5

Switching point

Fully adjustable

Contact

Microswitch

Contact rating

AC 250 V, 3 A, 500 VA



Versions

	Pressure range	Part no.
Differential pressure switch DS 01	0/0.6 bar	88103
Differential pressure switch DS 01	0/1 bar	88104
Differential pressure switch DS 01	0/1.6 bar	88105
Differential pressure switch DS 01	0/2.5 bar	88107
Differential pressure switch DS 01	0/4 bar	88106

Blue part no. = in-stock items