



CAPBs® pressure transmitter PT 70

- Application**
- Pressure tests of oil pipes
 - Tightness tests/strength tests of drinking water installations as per ZVSHK
 - Pressure loss test
 - Pressure test at pipe systems
 - Stress pressure test at pipe systems

Description Pressure transmitter for measurements in liquids and corrosive media.

Technical specifications

Dimensions
W x H x D: 42 x 76 x 35 mm

Weight
55 g

Interface
Bluetooth® Smart

Measuring ranges
0 / +25 bar

Accuracy
0.5 % of full scale
±1 digit

Resolution
0.1 bar

Hose connection
Plug connection DN 5



CAPBs® pressure and temperature FP 10

- Flow rate measurement (Pitot tube)
- Surface loss
- Ventilation loss (Pitot tube)
- 4 Pa measurement (hose kit)
- Heating system check 2.0 (Pitot tube)

Sensor module for simultaneous, continuous measurement of temperature and pressure. The CAPBs® allows for convenient flow rate measurement with a stable zero point.

Dimensions
W x H x D: 42 x 74 x 35 mm

Weight
33 g

Interface
Bluetooth® Smart

Measuring ranges
-20 / +20 mbar
0.2 / 20 m/s
-50 / +600 °C

Accuracy
±0.003 mbar
0.5 % displayed value ±1 digit
±0.1 m/s or ±5 % displayed value
±1.5 °C

Resolution
0.0001 mbar / 0.01 m/s / 0.1 °C



DG: H, PG: 4	Part no.	Price €
CAPBs® base handle BG 10	M091000017	
Pressure transmitter CAPBs® sens PT 70, 25 bar	M090142810	
Pressure/temperature CAPBs® sens FP 10	M090053210	
Accessories		
Hose kit SLS 4 Pa Test	500664	
Pitot tube EP-SR	500663	
Surface probe TFB-OF 120	522991	