



Modular base handle CAPBs® device with display



Benefits

- Charging during measurements thanks to mains connection via interface module



Versions

	DG	PG	Part no.	Price (€)*
Modular base handle CAPBs® device with interface basic IF 10	H	4	P00052	369.00
Modular base handle CAPBs® device with interface logger IF 20	H	4	P00100	454.00
IF 20	H	4	M094003911	158.00
Wall bracket CAPBs® device	H	3	511263	76.07

* prices plus applicable VAT Blue part no. = in-stock items

Description

Modular display and control unit for all CAPBs® sensors. The TFT colour display shows the measured values of the installed CAPBs® sensor in real-time. CAPBs® device is equipped with navigation key, magnets at the rear and a sounder for signals specific to certain measured values. The integrated lithium ion battery supplies the CAPBs® device with power.



Technical specifications

Dimensions

W x H x D: 62 x 155 x 42 mm

Weight

300 g

Display

TFT colour display

2.4 "

W x H: 38 mm 50 mm

240 x 320 pixels

Supply voltage

Lithium-ion battery (3.6 V/1,600 mAh)

Power supply unit (USB-C)

Battery or mains

Hours of operation

Depending on CAPBs® sens sensor module used

Interface

Bluetooth®

QR code (iOS, Android)

USB-C (Windows)

Degree of protection

IP 54 (EN 60529) with plugged in CAPBs® sens and CAPBs® interface